



DIMMABLE SURFACE SERIES

LED Surface Mounted Ceiling Lights IP65



Product Features

- Input voltage: 240V AC 50/60Hz
- Wattage: 13W
- Material: aluminium
- Epistar COB LED chip
- Power factor: 0.9
- Ambient temp: -20 to 40°C
- Suitable for dimming
- Recommended Universal Trailing Edge and Leading Edge dimmers
- Suitable for 2-way switching
- 3 year replacement warranty

Recommended dimmers: (2-8 pcs /dimmer)

- (1) CLA LYNX
- (2) CLA-VELA
- (3) Clipsal 32ELEDM
- (4) Clipsal 31E2PUDM
- (5) Clipsal 32E450UDM
- (6) Clipsal 32E450LM
- (7) HPM CAT250L
- (8) HPM CAT250T
- (9) HPM CAT400T



Technical data

CODE	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	BEAM ANGLE	IP	DIMM	DIAM (mm)	DEPTH (mm)	CARTON QTY
SURFACE13	13W GLOSS WH LED S/M CEILING LIGHT 3000K	3000	800	13	>80	40°	IP65	YES	Ø105	146	1/12
SURFACE14	13W GLOSS WH LED S/M CEILING LIGHT 5000K	5000	900	13	>80	40°	IP65	YES	Ø105	146	1/12
SURFACE15	13W GLOSS BLK LED S/M CEILING LIGHT 3000K	3000	800	13	>80	40°	IP65	YES	Ø105	146	1/12
SURFACE16	13W GLOSS BLK LED S/M CEILING LIGHT 5000K	5000	900	13	>80	40°	IP65	YES	Ø105	146	1/12